ered component esp. connecting rod - having split bearing aperture, in which

bearing aperture-forming components are separately pressed and sintered

POriginal Title: DE3904020A1: Verfahren zum Herstellen von Bauteilen mit geteiltem Lagerauge

PAssignee: BAYERISCHE MOTOREN WERKE AG Standard company

Other publications from BAYERISCHE MOTOREN WERKE AG

(BAYM)...

ANGERER S; PInventor:

1990-254873 / 199034

Update:

₽IPC Code: B22F 7/06:

₽Derwent Classes:

M22; P53;

PManual Codes:

M22-H03G(Powder metal products)

(DE3904020A) In the prodn. of sintered components with split bearing apertures, esp. i.c. **[®]Derwent** engine connecting rods, the bearing aperture-forming components are separately pre-pressed Abstract:

and sintered and then than components are assembled in a sizing mould to form the bearing

aperture and subjected to post-pressing (sizing).

Advantage - Mfg. costs are reduced compared with processes involving machining and

cryogenic fracture to form the split apertures.

Dwg.0/2

영Family: **PDF Patent** Pub. Date Derwent Update Pages Language IPC Code

DE3904020A * 1990-08-16 199034 German

Local appls.: DE1989003904020 Filed:1989-02-10 (89DE-3904020)